

## **PEDESTALS**

### **Classification**

A. Pedestals for office desks

#### **A1. Pedestal Types**

A.1.1. Melamine pedestals type «E», with simple drawer guide rails

A.1.2. Melamine pedestals, with telescopic drawer guide rails

A.1.3. Pedestals made of metal, or with metal carcass and cover made of melamine or compact laminate or plywood with HPL covering, or MDF with HPL covering

A.1.4. Pedestals made of chipboard with veneer coating

A.1.5. Pedestals made of MDF with artificial veneer (film) coating

A.1.6. Pedestals made of MDF with white lacquer

#### **A.2. Technical Data**

A.2.1. All Pedestals have metal drawers.

A.2.2. In all pedestals the drawer guide rails are invisible, hidden by the drawers

A.2.3. In all pedestals (except type “E”), the drawers are equipped with anti-tilt system, which prevents a second drawer from opening, when a first is already open.

A.2.4. All pedestals have a system to keep the drawers in closed position (except type “E”).

A.2.5. In type “E” and computer pedestals with non-telescopic guide rails, the drawers open up to 70%. In all other types the drawers open up to 100% and have a soft closing system.

A.2.6. All pedestals except some of type “E” have a separate drawer-stationery tray. In pedestals that do not have a separate stationary tray, an additional plastic tray is added in the top drawer.

A.2.7. All pedestals are produced in two depths: a) 60 cm, b) 80 cm.



A.2.8. All pedestals with 80 cm depth have drawer guide rails for full 100% drawer opening.

A.2.9. All pedestals with folder holders have drawer guide rails for full 100% drawer opening.

A.2.10. The sheet metal for drawers is 0,9mm thick, except pedestal type “E” which has 0,6mm.

A.2.11. Drawer weight loading:

- With simple guide rails: 20 kg
- With telescopic guide rails 30 kg

A.2.12. Pedestals can be movable with castors or stationary with glides. In the case of movable containers it is optionally possible to have castors with brakes.

A.2.13. In melamine pedestals, the complete carcass is made of double-side melamine film covered 3-layer chipboard, class E1, 18 mm thick.

A.2.14. In pedestals made of natural or artificial veneer, or lacquered, the carcass is made of 19 mm thick MDF.

A.2.16. All pedestals are equipped with a central safety lock.

A.2.17. All pedestals for PCs are equipped with two grommets for cable exit.

A.2.18. In pedestals with width of 1.200mm, a ventilation louver for the PC unit is added to the rear wall.

A.2.19. Sizes, shapes and colors from the catalogue of DROMEAS.

Packaging of 1 melamine pedestal with telescopic guide rails, dimensions 433x600x650H

Weight: 35,0 kg

Volume: 0.16 m<sup>3</sup>

Packets: 1

## PRODUCT CERTIFICATES:

EN 14073-2:04

EN 14073-3:04



