

Classification

A. Office swivel chair SMART (with castors)

A.1. Technical Data

A.1.1. The star base of the chair has a diameter of 660 mm and is made of die-cast aluminium. The surface finish can be either powder coated or polished.

A.1.2. It has twin castors made of polyamide, with a protective cover made of the same material..

A.1.3. The activation of the height adjusting gas lift is achieved through a lever which is accessible sideways under the seat. The range of the height-adjusting mechanism is 120mm.

A.1.4. The seating mechanism is Synchro-mechanism. It allows the simultaneous dynamic movement of the seat by 11o and the backrest by 18o and provides 5 locking positions. The mechanism is equipped with an «anti-panic» function and can be adjusted according to the user weight. The activation and deactivation of the Synchro motion is achieved through the same lever that is used for the seat height adjustment. The weight adjustment is achieved through a regulator screw which is positioned in front of and under the seat area.

A.1.5. The seating plate is made of thermoplastic polyamide (PA6). On the seating plate lies a cushion made of expanded polyurethane foam with 60mm thickness, which is upholstered with the chosen fabric. There is an option to adjust the seating plate's depth from 0-60mm and provides 7 locking positions.

Seat dimensions: width 460 mm, depth 410 mm.

A.1.6. The backrest is available in 3 versions: large, middle and with mesh.

A.1.6.1. In the first version we have an anatomic frame of formed and welded steel profiles, on which we place an internal mesh in such a way to distribute the pressure uniformly. It is connected with the relax mechanism through a steel corner blade. The back also contains a lumbar supprt that can be adjusted in height by 70mm.

Large backrest dimensions: height 740 mm, width 480 mm.

A.1.6.2. The second version follows the same construction principles of the first, the only difference being the size. Middle backrest dimensions: height 580 mm, width 480 mm.

A.1.6.3. The third version, mesh backrest, consists of an anatomical frame made of formed and welded steel profiles, over which a mesh backrest is applied, in a way that ensures even pressure distribution. The mesh backrest is mounted to the Synchro mechanism through a formed steel plate. The mesh backrest is equipped with an integrated lumbar support, height adjustable up to 70 mm.

Mesh backrest dimensions: height 660 mm, width 480 mm.

A.1.7. The seat armrests are made of thermoplastic polyamide and adjustable in height with a 70 mm adjustment range (175-245 mm from the seat). The upper part of the arms has a dimension of 250X90 mm and can be rotated +/- 15°. The contact surface of the arms is made of cast polyurethane of medium hardness for greater comfort and ergonomics and can also be moved back and forth in 6 positions (5 scales). Finally, it is possible to move the arms across the width of the adjustment range 460-510mm.

A.1.8 Executive chairs can also have a headrest, constructed by thermoplastic material, polyurethane foam and upholstered with the same fabric as the seating plate.

Upholstery choice out of 7 fabric groups with a large variety of colors.

Packaging 1 piece in carton box

Weight: 16,0 kg

Volume: 0.44 m³

PRODUCT CERTIFICATES:

EN 1335-1:02

EN 1335-2:10

EN 1335-3:09

DIN 4550/12.04

